






Americor Electronics Ltd. - 675 S. Lively Blvd. - Elk Grove Village, Illinois 60007
 Tel.: [847] 956-6200 - Fax.: [847] 956-0300 - Toll Free: [800] 830-5337 - E-mail: info@americor-usa.com - www.americor-usa.com









IEC Power Inlet 320 - C6

Specifications:

Power Rating: Domestic: 2.5 Amp. 125 / International: 2.5 Amp.250 Volt
Insulation Resistance: DC 500 Volt 100 Ω (min)
Dielectric Strength: 2000 VAC / 1 Minute
Housing Material: Nylon 6.6 UL 94V-0 or 94V-2
Manufacturers Specification: EN 60320; UL 817 - 498

Part Numbers: AEL-Part Number - X1 - X2	Termination (X1)		Panel Thickness (X2) only if applicable	
	Example AEL-JR-307 (E Type) - 4 - 20	0	Solder Terminals	10
[Part Number AEL-JR-307 (E-Type) with PCB Terminals and a Panel Thickness of 2 mm]	1	2.8 mm Quick Disconnect Terminals	15	1.50 mm
	2	4.8 mm Quick Disconnect Terminals	20	2.00 mm
	3	6.4 mm Quick Disconnect Terminals	30	3.00 mm
	4	PCB Terminals		

Configuration	Mounting	Part Number	Termination X1					Panel Thick. X2				Approvals	Click for Print	
			0	1	2	3	4	10	15	20	30			
	Flange Mounting	AEL-JR-307-S (S-Type)	X											

	Flange Mounting	AEL-WS-083-S-1A	X	X	X										
	Snap-In Mounting	AEL-WS-083-S-3	X		X					X					
	Slide-In Panel Mounting	AEL-WS-083-S-2	X		X										
	Slide-In Panel Mounting	AEL-JR-307 (E Type)						X	X	X	X	X		