Americor Electronics Ltd. - 675 S. Lively Blvd. - Elk Grove Village, Illinois 60007
Tel.: [847] 956-6200 - Fax.: [847] 956-0300 - Toll Free: [800] 830-5337 - E-mail: info@americor-usa.com - http://www.americor-usa.com

IEC 320-C13Power Outlet Strips
IEC 320 / C13-C14 Outlet/Inlet Strips

Specifications

Power Rating:	Domestic: 15 Amp. 125 Volt / International: 10 Amp. 250 Volt
Insulation Resistance:	DC 500 Volt 100 Ω (min)
Dielectric Strength:	2000 VAC / 1 Minute
Housing Material:	Nylon 6.6; UL 94 V-0 or 94 V-2
Standard:	EN 60320: UL 817 - 498

Part Numbers:
AEL-Part Number - X1-X2-X3

Example:
AEL-JR201SD-PCB 4-3-15
X1 4 = PCB Terminals
X2 B = 3.5mm length Terminals
X3 15 = for 1.5mm panel thickness

Termination (X1)		PCB Terminal Length (X2)		Panes Thickness (X3)	
0	Solder Terminals	A	3.02mm	08	0.8mm
1	2.8mm Quick Disconnect	B	3.50mm	10	1.0mm
2	4.8mm Quick Disconnect	C	5.30mm	15	1.5mm
3	6.3mm Quick Disconnect	D	6.80mm	12	2.0mm
4	PCB Terminals	E	10.8mm	25	2.5mm

Configuration	Mounting	Part Numbers	X1					X2					X3					Approvals	Click for Print
			0	1	2	3	4	A	B	C	D	E	08	10	15	20	25		
2 - 7 Positions	Snap - In Mounting	AEL-JR-302G2-(15)	X		X				X						X	X	X	cULus VDE	
		AEL-JR-302G3-(15)																	
		AEL-JR-302G4-(15)																	
		AEL-JR-302G5-(15)																	
		AEL-JR-302G6-(15)																	
		AEL-JR-302G7-(15)																	
1+1 to 1+5 Positions	Snap - In Mounting	AEL-JR-3014G11-(15)	X		X				X						X	X	X	cULus VDE	
		AEL-JR-3014G12-(15)																	
		AEL-JR-3014G13-(15)																	
		AEL-JR-3014G14-(15)																	
		AEL-JR-3014G15-(15)																	