



Index North America Part 3



Description

IEC 309 Plugs and Connectors

*

Plug No.

IEC 309 Plug Splash Proof 16 amp 100-130 Volt	WS 309 P 16 125 V
IEC 309 Connector 16 amp 100-130 Volt	WS 309 C 16 125 V
IEC 309 Plug Splash Proof 16 amp 250 Volt	WS 309 P 16 250 V
IEC 309 Connector 16 amp 250 Volt	WS 309 C 16 250 V
IEC 309 Plug Splash Proof 32 amp 100-130 Volt	WS 309 P 32 125 V
IEC 309 Plug Splash Proof 32 amp 250 Volt	WS 309 P 32 250 V
IEC 309 Connector with spring Loaded Cover , 32 amp. 125 Volt	WS 309-3P32 125 V
IEC 309 Connector with spring Loaded Cover , 32 amp. 250 Volt	WS 309-3P32 125 V

*

IEC 320 Hooded Male

*

Hooded Male Plug 3 Conductor, IEC 320 - C2 Straight	WS - 149
Hooded Male Plug 3 Conductor, IEC 320 - C6 Straight	WS - 134
Hooded Male Plug 2 Conductor, IEC 320 - C18 Straight	WS - 003E
Hooded Male Plug 3 Conductor, IEC 320 - C14 Straight	WS - 003C
Hooded Male Plug 3 Conductor, IEC 320 - C14 Right	WS - 003C 1
Hooded Male Plug 3 Conductor, IEC 320 - C14 Left	WS - 003C 2
Hooded Male Plug 3 Conductor, IEC 320 - C14 Front Ground top	WS - 003C R
Hooded Male Plug 3 Cond., IEC 320 - C14 Front Ground Bottom	WS - 003C L
Hooded Male Plug 3 Conductor, EC 320 - C20 Straight	WS - 003D
Hooded Male Plug 3 Conductor, IEC 320 - C20 Right	WS - 003D R
Hooded Male Plug 3 Conductor, IEC 320 - C20 left	WS - 003D L